

Appl. No. 09/867,893  
Amendment and/or Response  
Reply to Office action of 14 May 2004

Page 3 of 10

**Amendments to the Specification:**

Please replace the paragraph beginning at page 1, line 12 with the following rewritten paragraph:

Such a data carrier of the type defined in the opening paragraph is known from the document ~~WO 00/26868~~ US Patent 6,507,130, "DATA CARRIER WITH PROTECTION AGAINST SPY OUT", issued 14 January 2003 to Peter Thueringer and Edgar Rieger and is formed by a transponder of a smart card. The known data carrier is adapted to communicate communication data from or to a base station via a contact pad of the smart card. The data carrier has processing means for processing the communication data received via the contact pad or to be output via the contact pad.

Please replace the paragraph beginning at page 4, line 7 with the following rewritten paragraph:

The data carrier 2 includes processing means 4 for processing the communication data KDI received from the base station and the communication data KD2 to be transferred to the base station. The processing means 4 include, for example, a microprocessor of the type 80C51, a co-processor for encrypting and decrypting confidential information or data, memory means (ROM) for the storage of a processing program and intermediate memory means (RAM).

Please delete the Abstract of the invention in its entirety, and add the following new Abstract:

**Appl. No. 09/867,893**  
**Amendment and/or Response**  
**Reply to Office action of 14 May 2004**

**Page 4 of 10**

A data carrier that communicates confidential data is configured to mask process-dependent power consumption by using power stored in an internal capacitor. The capacitor is initially charged to the voltage of an external power source, and then decoupled from the external power source. The capacitor provides power to an internal processor, and consequently discharges gradually. At the end of a given time interval, the capacitor is discharged to a fixed voltage, then charged to the supply voltage. In this manner the power consumed by charging of the capacitor is decoupled from the power consumed by the processor. If the capacitor drops below a threshold voltage before processing is completed, the processor is halted. To optimize the available processing time, the time interval before discharging the capacitor to the fixed voltage is dynamically adjusted to reduce the time that the processor is halted.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**